
callsun

495W-515W

N-Type Bifacial Dual-Glass Module



515w / MAXIMUM POWER OUTPUT

23.1 % / MAXIMUM MODULE EFFICIENCY

20 Year / PRODUCT WARRANTY

30 Year / LINEAR POWER WARRANTY

N-Type SMBB Technology

Combines N-type cells with SMBB technology to improve current collection, reduce resistive losses, and enhance long-term reliability.

Bifacial Power Gain

Bifacial cells capture rear-side reflected light for up to 30% additional energy under favorable conditions, with durable dual-glass protection.

Advanced AR Coating & Optimized Grid Mesh

Dual-layer front AR coating and an optimized rear-glass grid enhance light capture and reflection for improved energy output.

PID Resistance

Optimized cell technology and high-quality encapsulation help resist potential-induced degradation (PID) in hot and humid environments.


0.4% Annual Degradation

≤1% power degradation in the first year and ≤0.4% annually thereafter, backed by a 30-year linear power warranty.

Lower LCOE

High module efficiency and a -0.29%/°C power temperature coefficient support higher energy yield and lower overall system costs.

Performance Warranty



1% First-year Degradation

0.4% Annual Degradation

* Please refer to product warranty for details

- IEC 61215, IEC 61730
- ISO 9001: 2023 Quality management systems
- ISO 14001: 2023 Environmental management systems
- ISO 45001: 2023 Occupational health and safety management systems

callsun

© 2026 ZOOMSUN ENERGY LIMITED. All rights reserved.


Disclaimer: Specifications included in this datasheet are subject to change without notice.
Please contact our technical team for the latest version.

MECHANICAL CHARACTERISTICS

Cell Type	N-Type Monocrystalline
No. of Cells	108 (9 × 6) × 2
Dimensions	1962 × 1134 × 30 mm (77.24 × 44.65 × 1.18 inches)
Weight	26.69 kg (58.84 lb)
Front Glass	2.0 mm (0.08 inches), Anti-reflection Coating
Back Glass	2.0 mm (0.08 inches), Heat Strengthened Glass
Frame	30 mm (1.18 inches), Anodized Aluminium Alloy
Junction Box	IP 68 rated (3 bypass diodes)
Output Cables	4.0 mm² / 12 AWG ±1200 mm or Customized Length
Connector	Staubli MC4-EVO2 (IP68, 1500V DC)
Fire Rating	Type 29 (UL)
Safety Class	Class II

ENGINEERING DRAWINGS

Unit: mm



PACKAGING CONFIGURATION


Palletized Dimensions (L × W × H)	1975 × 1120 × 1260mm
Modules per Pallet	36 pcs
Modules per 40' HQ Container	864 pcs

APPLICATION CONDITIONS

Operational Temperature	-40°C ~ +85°C (-40°F ~ +185°F)
Maximum System Voltage	1500 V DC (UL)
Max. Series Fuse Rating	30 A

CHARACTERISTIC CURVES

CS515-M2HD2609



ELECTRICAL CHARACTERISTICS (STC/BNPI)

Type	CS495-M2HD2609		CS500-M2HD2609		CS505-M2HD2609		CS510-M2HD2609		CS515-M2HD2609	
Testing Condition	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI
Maximum Power - Pmax (Wp)	495	548.46	500	554.00	505	559.54	510	565.08	515	570.62
Open-circuit Voltage - Voc (V)	39.83	40.03	39.99	40.19	40.16	40.36	40.32	40.52	40.48	40.68
Short-circuit Current - Isc (A)	15.83	17.54	15.92	17.64	16.01	17.74	16.10	17.84	16.19	17.93
Maximum Power Voltage - Vmp (V)	33.10	/	33.22	/	33.33	/	33.45	/	33.56	/
Maximum Power Current - Imp (A)	14.95	/	15.05	/	15.15	/	15.25	/	15.34	/
Module Efficiency (%)	22.2	/	22.5	/	22.7	/	22.9	/	23.1	/
Temperature Coefficients of Pmax	-0.29% / °C									
Temperature Coefficients of Voc	-0.25% / °C									
Temperature Coefficients of Isc	0.045% / °C									

STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5
STC-Pmax [W]/Tolerance: ±3%, Voc [V] /Tolerance:±3%, Isc [Adc] /Tolerance:±3%
BNPI: Front Irradiance 1000W/m², Back Irradiance 135W/m², Cell Temperature 25°C, AM=1.5
BNPI-Pmax [W]/Tolerance: ±3%, Voc [V] /Tolerance:±3%, Isc [Adc] /Tolerance:±3%

ELECTRICAL CHARACTERISTICS (NMOT)

Type	CS495-M2HD2609	CS500-M2HD2609	CS505-M2HD2609	CS510-M2HD2609	CS515-M2HD2609
Testing Condition	NMOT	NMOT	NMOT	NMOT	NMOT
Maximum Power - Pmax (Wp)	376.9	380.7	384.4	388.2	390.8
Maximum Power Voltage - Vmp (V)	30.95	31.07	31.19	31.32	31.32
Maximum Power Current - Imp (A)	12.17	12.25	12.33	12.40	12.45
Open-circuit Voltage - Voc (V)	37.78	37.94	38.11	38.16	38.33
Short-circuit Current - Isc (A)	12.77	12.84	12.91	12.99	13.06

NMOT: Irradiance 800W/m², Ambient Temperature 20°C, AM=1.5, Wind speed 1m/s

callsun

© 2026 ZOOMSUN ENERGY LIMITED. All rights reserved.

Disclaimer: Specifications included in this datasheet are subject to change without notice.
Please contact our technical team for the latest version.